



- WILL ACCEPT (20) MULTIMATE AND 2 TYPE XII PIN CONTACTS.
- CAVITY IDENTIFICATION ON FRONT AND REAR FACE.
- NUMBER 4 FASTENERS RECOMMENDED FOR MOUNTING.
- HOUSING: NYLON, BLACK. PERIPHERAL SEAL: ELASTOMER, GRAY.
- APPLIES TO 206613-6 ONLY.
- PERMANENT WHITE MARKED OR WHITE INK STAMPED CAVITY IDENTIFICATION.
- HOUSING: NYLON, RED. PERIPHERAL SEAL: ELASTOMER, GRAY.
- WHITE DOT NEAR POSITION 1 ON WIRE ENTRY FACE.

PRELIMINARY	8/4	-	YES	A	1-206613-2
PRELIMINARY	7/4	-	YES	A	206613-9
	6/4	-	YES	A	206613-7
	4	4	NO	A	206613-6
	4	-	YES	A	206613-5
	4	-	NO	B	206613-3
	4	-	NO	A	206613-1
NOTES	THREADED INSERTS	PERIPHERAL SEAL	SEE DETAIL	PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DW	M. BINNER	05/26/94	Tyco Electronics Corporation Harrisburg, PA 17105-3608
		CHK	R. STONE	6-23-94	
DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:	Tyco Electronics Corporation			
INCHES		PRODUCT SPEC	RECEPTACLE HOUSING, STANDARD SEX, SHELL SIZE 23, CPC		
		APPLICATION SPEC	108-10024		
		SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
		WEIGHT	A1	00779	206613
MATERIAL	FINISH	CUSTOMER DRAWING			
		SCALE	2:1	SHEET	1 OF 1
		REV			P1