



1. THE CONTACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT.
2. ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY UNLESS OTHERWISE SPECIFIED.
3. MATERIAL:
  - HOUSING - THERMOPLASTIC (BLACK)
  - TERMINALS - HIGH STRENGTH COPPER ALLOY PLATED WITH .000030 MIN GOLD, OR GOLD FLASH OVER .000030 MIN PALLADIUM NICKEL, ON CONTACT MATING SURFACE. .000050 MIN NICKEL UNDERPLATE OVER ENTIRE TERMINAL.
4. WIRE SIZE: 28-27-28 AWG 7 STRANDS OF COPPER CONDUCTORS. MAX INSULATION .045 IS ACCEPTABLE FOR MOST APPLICATIONS.

△ CORING MAY OR MAY NOT APPEAR AND IS AT THE DISCRETION OF TYCO ELECTRONICS.

REV	DATE	REVISIONS	DATE	BY
GP 00	12-28-79	REVISION	9/24/07	ZYR/WLM
K		REVISED PER ECO-06-00653		

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE	12-28-79	BY	A.HOLT
DIMENSIONS IN CHARS		DATE	12-28-79	BY	M.O. FRIEL
TOLERANCES UNLESS OTHERWISE SPECIFIED		DATE	12-28-79	BY	W.D. WARD
APPROVALS		DATE		BY	
DESIGN		DATE		BY	
CHECKED		DATE		BY	
CUSTOMER DRAWING		DATE		BY	