



1. THE CONTACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT.
 2. ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY UNLESS OTHERWISE SPECIFIED.
 3. MATERIAL:
 - HOUSING - THERMOPLASTIC (BLACK)
 - TERMINALS - HIGH STRENGTH COPPER ALLOY PLATED WITH .000030 MIN GOLD, OR GOLD FLASH OVER .000030 MIN PALLADIUM NICKEL, ON CONTACT MATING SURFACE. .000050 MIN NICKEL UNDERPLATE OVER ENTIRE TERMINAL.
 4. WIRE SIZE: 26, 27, OR 28 AWG 7 STRANDS OF COPPER CONDUCTORS, MAX INSULATION ϕ .045 IS ACCEPTABLE FOR MOST APPLICATIONS.
5. CORING MAY OR MAY NOT APPEAR AND IS AT THE DISCRETION OF TYCO ELECTRONICS.

REV	DATE	DESCRIPTION	BY	CHK'D
00				
01	9/24/07		ZYR/WLM	

THIS DRAWING IS A CONTROLLED DOCUMENT		DATE		REV	
DIMENSIONS IN CHARS		3-4-81		1	
TOLERANCES UNLESS OTHERWISE SPECIFIED		3-30-81		1	
APPROVALS		DATE		BY	
DESIGNED BY		3-30-81		Z	
CHECKED BY					
DRAWN BY					
APPLICATION SPEC					
RECORD					
CUSTOMER DRAWING		A2100779		552469	

AS SHOWN	552469-1
DESCRIPTION	PART NO