



1. THE CONTACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT.
2. ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY UNLESS OTHERWISE SPECIFIED.
3. MATERIAL:  
HOUSING - THERMOPLASTIC (BLACK)  
TERMINALS: - HIGH STRENGTH COPPER ALLOY PLATED WITH .000030 MIN GOLD OR GOLD FLASH OVER .000030 MIN PALLADIUM NICKEL ON CONTACT MATING SURFACE. .000050 MIN NICKEL UNDERPLATE OVER ENTIRE TERMINAL.
4. WIRE SIZE: 24 & 26 AWG SOLID & 24 AWG 7 STRANDS OF COPPER CONDUCTORS. MAX INSULATION DIAMETER OF .045 IS ACCEPTABLE FOR MOST APPLICATIONS.

△ CORING MAY OR MAY NOT APPEAR AND IS AT THE DISCRETION OF TYCO ELECTRONICS.

REV	DATE	DESCRIPTION	BY	CHK	APP
00	12/10/04	REVISED FOR ESD-06-00253	J	ZR	WM

AS SHOWN	552312-1
DESCRIPTION	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT		DATE	12-20-79	BY	A.HOLT
DIMENSIONS IN INCHES		APPROVED	1-1-80	BY	V.E.S.
TERMINAL SPECIFICATIONS		APPROVED	1-1-80	BY	W.M.
MATERIAL		APPROVED		BY	
CUSTOMER DRAWING		SCALE	NIS	SHEET	1 OF 1