



1. THE CONTACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT.
  2. ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY UNLESS OTHERWISE SPECIFIED.
  3. MATERIAL:
    - HOUSING - THERMOPLASTIC (BLACK)
    - TERMINALS: - HIGH STRENGTH COPPER ALLOY PLATED WITH .000030 MIN GOLD OR GOLD FLASH OVER .000030 MIN PALLADIUM NICKEL ON CONTACT MATING SURFACE. .000050 MIN NICKEL UNDERPLATE OVER ENTIRE TERMINAL.
  4. WIRE SIZE: 24 & 26 AWG SOLID & 24 AWG 7 STRANDS OF COPPER CONDUCTORS. MAX INSULATION DIAMETER OF .045 IS ACCEPTABLE FOR MOST APPLICATIONS.
- △ CORING MAY OR MAY NOT APPEAR AND IS AT THE DISCRETION OF TYCO ELECTRONICS.

REV	DATE	DESCRIPTION	BY	CHKD	DATE	APP'D
00						
N		REVISED PER EOP-06-00853			2/1/00/04	ZR/VM

DIMENSIONS		TOLERANCES		FINISHES	
0	AS	0	AS	0	AS
1	AS	1	AS	1	AS
2	AS	2	AS	2	AS
3	AS	3	AS	3	AS
4	AS	4	AS	4	AS
5	AS	5	AS	5	AS
6	AS	6	AS	6	AS
7	AS	7	AS	7	AS
8	AS	8	AS	8	AS
9	AS	9	AS	9	AS
10	AS	10	AS	10	AS

THIS DRAWING IS A CONTROLLED DOCUMENT.	DATE	BY	DESCRIPTION
12-19-79	12-19-79	12-28-79	12-28-79
12-28-79	12-28-79	12-28-79	12-28-79
12-28-79	12-28-79	12-28-79	12-28-79
12-28-79	12-28-79	12-28-79	12-28-79
12-28-79	12-28-79	12-28-79	12-28-79
12-28-79	12-28-79	12-28-79	12-28-79
12-28-79	12-28-79	12-28-79	12-28-79
12-28-79	12-28-79	12-28-79	12-28-79
12-28-79	12-28-79	12-28-79	12-28-79

AS SHOWN	552283-1
DESCRIPTION	PART NO
TYCO ELECTRONICS CORPORATION	
24 POSITION, B SLOT	
CHARACTER W/ 4-40 HOLES	
CUSTOMER DRAWING	
SCALE	1" = 1"
SHEET	1 OF 1
REV	N