



1. THE CONTACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT.
2. ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY UNLESS OTHERWISE SPECIFIED.
3. MATERIAL:
HOUSING - POLYPHENYLENE
TERMINALS: - HIGH STRENGTH COPPER ALLOY PLATED WITH .000030 MIN GOLD OR GOLD FLASH OVER .000030 MIN PALLADIUM NICKEL ON CONTACT MATING SURFACE. .000050 MIN NICKEL UNDERPLATE OVER ENTIRE TERMINAL.
4. WIRE SIZE: 24 & 26 AWG SOLID & 24 AWG 7 STRANDS OF COPPER CONDUCTORS. MAX INSULATION DIAMETER OF .045 IS ACCEPTABLE FOR MOST APPLICATIONS.

△ CORING MAY OR MAY NOT APPEAR AND IS AT THE DISCRETION OF TYCO ELECTRONICS.

THIS DRAWING IS A CONTROLLED DOCUMENT		DATE		REV	
DIMENSIONS IN CHARGES		MATERIAL		CUSTOMER DRAWING	
0	AS	0	AS	0	AS
1	AS	1	AS	1	AS
2	AS	2	AS	2	AS
3	AS	3	AS	3	AS
4	AS	4	AS	4	AS
5	AS	5	AS	5	AS
6	AS	6	AS	6	AS
7	AS	7	AS	7	AS
8	AS	8	AS	8	AS
9	AS	9	AS	9	AS
10	AS	10	AS	10	AS

BLACK	552314-1
COLOR	PART NO

DATE	12-26-79	BY	MM
DESIGNED BY	STEPHEN DOSS	12-21-79	
APP. ENGINEER	M.O. FRIEL	1-2-80	
PRODUCT SPEC			
APPLICATION SPEC			
RECORD			
CUSTOMER DRAWING			

Tyco Electronics Corporation
 1700 Electronics Corporation
 Harrisburg, PA 17105-8688

ASSEMBLY RECEPTACLE
 36 POSITION, B SIDE
 CHAMFER LOCK W/ 4-40 HOLES
 REMINGTON TO

SCALE: NTS
 SHEET 1 OF 1