



HGC 15 M/M GENDER CHANGER

PIN OUT: 15Male

15Male

1	-----	1
2	-----	2
8	-----	8
10	-----	10
15	-----	15
G	-----	G

Label: yellow color with black character

One side: MINI GENDER CHANGER

The other side: U.S.A. PATENT 5199906 ORDER CHANGER

SPECIFICATION

INSULATOR: PBT Glass fibre reinforced UL 94 V0

CONTACT: Brass

CONTACT PLATING: Gold plated over nickel

SHELL: Tin plated shell

CURRENT RATING: 3 AMP

DIELECTRIC STRENGTH: 1000V AC FOR ONE Minute

INSULATOR RESISTANCE: 1000MΩ min at 500V DC

TEMPERATURE: -55°C → +105°C

				Edition	ASSMANN Electronics, Inc.			
				A2				
				SCALE	PART NO.		DWG NO.	DATE
				2:1	AB418-R		TH0013-03	1/Jul-2003
				UNIT	DRAWN		CHECKED	APPRD
				mm	Fu Hao			
Customer	REVISION	DESCRIPTION	DATE	Page	1/1			
	2	修改螺絲(螺絲5.2mm改為6.2mm)	2003/07/01					
	1	修改貼紙(R.O.C. PATENT 64341 <small>ORDER CHANGER</small> 改為MINI GENDER CHANGER)	2001/11/30					