




DESCRIPTION: 25-PIN MALE / MALE GENDER CHANGER

SPECIFICATION:


INSULATOR: PBT GLASS FIBER REINFORCED UL 94VO
 CONTACT: BRASS
 CONTACT PLATING: GOLD PLATED OVER NICKEL
 SHELL: TIN PLATED SHELL
 CURRENT RATING: 5 AMP
 DIELECTRIC STRENGTH: 1,000VAC FOR 1 MINUTE
 INSULATION RESISTANCE: 1,000 MegOHMS MIN @500 VDC
 TEMPERATURE: -55° C - +105° C

NOTE:

LABEL: YELLOW COLOR WITH BLACK CHARACTORS
 ONE SIDE: MINI GENDER CHANGER
 OTHER SIDE: U.S.A. PATENT 5199906



| 25-PIN MALE | 25-PIN MALE |
|-------------|-------------|
| 1 | 1 |
| 2 | 2 |
| 3 | 3 |
| ~ | |
| 24 | 24 |
| 25 | 25 |
| SHELL | SHELL |



DO NOT SCALE FROM DRAWING

RoHS COMPLIANT

| | | | | |
|----------------|---|-------------------|---------------------------|--------------------------|
| | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | | DRAWN: C. SMITH | DATE: 10-15-07 |
| | | | CHECKED: | DATE: |
| NorComp | SCALE: 1.5 : 1 | SHEET 1 | OF 1 | REV 1 |
| | DWG NO. GCLP25M25M | | | |