



No. of pos.	A	B	C	D	E	ØF	PART NO.
9	32.9	25.0	39.5	41.8	16.3	11.0	165X13369XE
15	41.2	33.3	45.5	47.8	16.3	11.0	165X13379XE
25	54.9	47.0	52.5	54.8	16.3	12.0	165X13389XE
37	71.4	63.5	55.0	57.8	18.7	15.0	165X13399XE
50	69.0	61.1	55.0	57.8	19.5	14.0	165X13409XE

Directive 2002/95/EC
 "RoHS"
 Compliant

HOOD ASSEMBLY CONSISTS OF:

- 1 x HOOD + COVER: PBT UL 94 V-0; BLACK
- 1 x PRESS INSERT: PBT UL 94 V-0; BLACK
- 2 x JACKSCREWS: BRASS; NICKEL PLATED
- 2 x SCREW FOR STRAIN RELIEF: STEEL; ZINC PLATED
- 2 x COVER SCREWS: STEEL; NICKEL PLATED
- 1 x STRAIN RELIEF: STEEL; NICKEL PLATED

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

TECHNICAL DATA:

- TEMPERATURE RANGE: -33°C to +90°C

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
 OWNERSHIP AND COPYRIGHT OF CONEC GmbH
 DO NOT ALTER CAD DRAWING BY HAND

tolerance		 dim. in mm
2006	date	name
drawn	06.02.	Lehmenkühler
appd.	06.02.	Mickenbecker
norm		
d-old		
a	Origin	
rev.	description	date name



scale: 1:1	
material: SEE DRAWING	
title: PLASTIC HOOD 9-50pos. WITH STRAIGHT CABLE EXIT big space inside	
dwg no: AutoCAD 2004	DIN-A
16K1A1736	
part no: SEE TABLE	
sh: 1/1	