



used for: D-SUB COMBINATION

NOTES:

1. METALSHELLS: STEEL; min. 320µ" TIN
2. INSULATORS: PBT GF UL 94 V-0, GREEN
3. = CRITICAL DIMENSION: SPC

Directive 2002/95/EC
RoHS
Compliant

| | | | | | |
|---|--------|---|--|-------------------------------------|--|
| tolerance | | scale: 2:1 (5:1) | | material: SEE NOTES | |
| 2001 | | name | | title: | |
| drawn | date | Parel | D-SUB COMBINATION FEMALE 3W/3S | | |
| appd. | 11.05. | E. Mickenbecker | | | |
| norm | 11.05. | E. Mickenbecker | | | |
| e-old | 11.05. | E. Mickenbecker | | | |
| rev. description | | date | | name | |
| THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GMBH DO NOT ALTER CAD DRAWING BY HAND | | | | | |
| | | dwg no: 13K1A246A AutoCAD 2000 DIN-A 3 | | part no: 3003W3SXX99A10X sh: 1/1 | |