used for: D-SUB COMBINATION









NOTES:

1. METALSHELLS: STEEL; min. 320µ" TIN
2. INSULATORS: PBT GF UL 94 V-0, GREEN
3. THREADED INSERT: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
4. COLLAR: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
5. MAXIMUM TORQUE VALUE FOR THREAD: 6" LBS
6. [ ] = CRITICAL DIMENSION: SPC

Directive 2002/95/EC „RoHS" Compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH
DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name

tolerance

	date	name
2001		
drawn	17.05.	Parei
appd.	17.05.	E. Mickenbecker
norm		
d-old		

scale: 2:1 (5:1)
material: SEE NOTES

title:
D-SUB COMBINATION FEMALE
8W8S
with threaded insert

dwg no: 13K1A253A
AutoCAD 2000 | DIN-A 3 | sh: 1/1

part no: 3008W8SXX99A30X