






<p>POS. 1</p>  <p>2x SCREW 4-40 UNC with allen wrench head</p>	<p>POS. 2</p>  <p>1x CABLE STRAIN RELIEF</p>
<p>POS. 3</p>  <p>2x COVER SCREW</p>	<p>POS. 4</p>  <p>2x CABLE STRAIN RELIEF SCREW</p>

**NOTES:**

1. HOOD: PBT GF UL 94 V0
2. SCREW 4-40 UNC: STEEL; NICKEL PLATED
3. SCREW FOR STRAIN RELIEF: STEEL; NICKEL PLATED
4. COVER SCREW: STEEL; NICKEL PLATED
5. STRAIN RELIEF: STEEL; NICKEL PLATED
6. FEMALE CONNECTOR 7W2, WITHOUT CONTACTS

Directive 2002/95/EC  
"RoHS"  
Compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

DO NOT ALTER CAD DRAWING BY HAND			
tolerance	ISO 2768-m	 dim. in mm	
date	name		
drawn	17.12.07	Schmidt	
appd.	17.12.07	Mickenbecker	
norm			
d-old			
a	Origin	<b>CONEC</b> <sup>®</sup>	
rev.	description	date	name

scale:	2:1	
material:	see notes	
title:		
<b>PLASTIC HOOD</b> with 7W2 Female Crimp Connector straight cable exit		
dwg no:	Inventor 10	DIN-A3
	13K1A2364	sh: 1
part no:	13-000210	