





<p>POS. 1</p>  <p>2x JACKSCREW 4-40 UNC with allen wrench head</p>	<p>POS. 2</p>  <p>1x CABLE STRAIN RELIEF</p>
<p>POS. 3</p>  <p>2x COVER SCREW</p>	<p>POS. 4</p>  <p>2x CABLE STRAIN RELIEF SCREW</p>

**NOTES:**

1. HOOD: PBT GF UL 94 V0
2. JACKSCREW 4-40 UNC: STEEL; NICKEL PLATED
3. SCREW FOR STRAIN RELIEF: STEEL; NICKEL PLATED
4. COVER SCREW: STEEL; NICKEL PLATED
5. STRAIN RELIEF: STEEL; NICKEL PLATED
6. FEMALE CONNECTOR 7W2, WITHOUT CONTACTS

Directive 2002/95/EC  
„RoHS“  
Compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

DO NOT ALTER CAD DRAWING BY HAND			
a	Origin		
rev.	description	date	name

tolerance	ISO 2768-m
	dim. in mm
date	name
drawn	17.12.07 Schmidt
appd.	17.12.07 Mickenbecker
norm	
d-old	
<b>CONEC</b> ®	

scale: 2:1	
material: see notes	
title: <b>PLASTIC HOOD</b> with 7W2 Female Crimp Connector straight cable exit	
dwg no: Inventor 10	DIN-A3
13K3A2364	
part no: 13-000370	sh: 1