


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
H	—		J	SR10-0382-02	23-08-02	KV	—
			K	SR10-0457-02	24-10-02	KV	—
			L	ECR-07-008767	16-07-07	BSV	KMA



NOTES:

- THIS RECEPTACLE ACCEPTS SIZE 20 REC. CONTACTS.
 - MAXIMUM WIRE INSULATION RECOMMENDED FOR USE WITH THIS RECEPTACLE IS 1,73 DIA. MAX..
 - RETENTION TINES ARE AN INTEGRAL PART OF INSERT.
 - FOLLOWING INSERTION/REMOVAL TOOLS ARE RECOMMENDED FOR USE WITH THESE CONNECTORS:
 32-28AWG/28-24AWG CONTACTS
 91067-3 INSERTION/REMOVAL
 726363-1 INSERTION ONLY
 24-20AWG CONTACTS
 726363-1 INSERTION ONLY
 726364-1 REMOVAL ONLY
- △5 INSERTS: GLASSFILLED SELF-EXTINGUISHING PBT, COLOR BLACK.
 △6 AMP DATE CODE, AMP PART NUMBER, INK STAMPED.
 △7 RAISED CAVITY IDENTIFICATION 0,8 HIGH.
 △8 RAISED CAVITY IDENTIFICATION NUMBERS ON WIRE SIDE ARE WHITENED FOR 164534-9.

OBSOLETE	BRIGHT TIN	BRIGHT TIN	STEEL	164534-9	△8
	BRIGHT TIN	BRIGHT TIN	STEEL	164534-4	
	PLATING FRONT SHELL	PLATING REAR SHELL	MATERIAL SHELLS	PARTNUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	11FEB99		Tyco Electronics Corporation 's-Hertogenbosch, Nederland
DIMENSIONS: mm		CHK	-		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	-		
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		PRODUCT SPEC	-		
MATERIAL		FINISH	-		NAME 37 POS HDP-20 RECEPTACLE CONNECTOR SIZE 4
		WEIGHT	-		SIZE A3 CAGE CODE - DRAWING NO C- 164534 RESTRICTED TO -
CUSTOMER DRAWING			SCALE	NTS	SHEET 1 OF 1 REV L