



- 1 POSITION NUMBERS SHOWN FOR REFERENCE ONLY.
- 2 MATERIAL
 MOLDED PARTS: POLYESTER, UL 94V-0 RATED, BLACK.
 CONTACTS: PHOSPHOR BRONZE.
 BRACKET: ZINC.
 BOARDLOCK: COPPER ALLOY.
- 3 FINISH
 CONTACTS: EITHER 0.76µm [.000030] MIN GOLD PLATE FOR A LENGTH OF 3.35 [.132] MIN FROM MATING END OR GOLD FLASH OVER 0.76µm [.000030] MIN PALLADIUM NICKEL PLATE FOR A LENGTH OF 3.35 [.132] MIN FROM MATING END. 3.81µm [.000150] MIN TIN-LEAD FOR A LENGTH OF 3.23 [.127] MIN FROM OPPOSITE END, ALL OVER 1.27µm [.000050] MIN NICKEL UNDERPLATE.
 BRACKET: 3.81 µm [.000150] MIN NICKEL OVER 5.08µm [.000200] MIN COPPER.
 BOARDLOCK: 5.08µm [.000200] MIN TIN-LEAD OVER 1.27µm [.000050] MIN NICKEL.
- 4 ACTUAL HOLE SIZE USED WILL DEPEND ON TRACE ROUTING REQUIREMENTS BETWEEN HOLES AND CONNECTOR PLACEMENT TECHNIQUE.

OBSOLETE	TRAY	750961-2
	TUBE	750961-1
	PACKAGING	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN H.MOLL 23 SEP 91	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm [INCHES]		CHK R.STONE 09 OCT 91	Tyco Electronics Corporation	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD -	NAME	
0 PLC ± -	1 PLC ± -	PRODUCT SPEC		
2 PLC ± 0.13[.005]	3 PLC ± -	108-1228		
4 PLC ± -	ANGLES ± -	APPLICATION SPEC		
MATERIAL		SIZE	CAGE CODE	DRAWING NO
FINISH		114-40029	A1	00779
CUSTOMER DRAWING		SCALE	SHEET	REV
		4:1	1 of 1	E