

1

2

3

4

A

B

C






D

A

B

C

D



PC board drilling dimensions
(after plating - thickness: 1.60 to 3.20 mm)

TIN LEAD PART NUMBER

PART NUMBER	
flash gold	D50P90C4PX00
0.76µ gold	D50P90C6PX00

LEAD FREE PART NUMBER

PART NUMBER	
flash gold	D50P90C4PX00LF
0.76µ gold	D50P90C6PX00LF

GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:
SEE DRAWING C01-8646-0001

European Views

www.fciconnect.com		surface ISO 1302 ✓	tolerance std ISO 406 ISO 1101	projection mm
TOLERANCES UNLESS OTHERWISE SPECIFIED				
Dr	PESSON	1996/07/24	ANGULAR	0.X ±0.1
Eng	PESSON	1996/07/24	LINEAR	0.XX ±0.1
Chr	LEGARE	1996/07/24	0.XX' ±2'	0.XXX ±0.1
Appr	LEGARE	1996/07/24	Product family	D-SUB
size				A3
Scale				2
ECN				LS06-0140
Spec ref				-
Title			MALE CONNECTOR DELTA D LOW PROFIL	Rev.
catalog no			-	D
dwg no			C01-8646-0464	sheet 1 of 1

rev	ecn no	dr	date
A	-	JAR	1996/07/24
B	LS05-004	MPE	2005/02/15
C	LS06-0097	LGO	2006/07/28
D	LS06-0140	LGO	2006/09/23
-	-	-	-
-	-	-	-
-	-	-	-

1

2

3

4



Copyright FCI.