



CHARACTERISTICS:

Max current rating:	7.5A per standard contact
Dielectric withstanding voltage:	1000V minimum
Insulation resistance:	≥5000Ma
Contact resistance:	≤7.3ma
Mating and unmating forces:	conform to MILC24308
Contact retention:	40N for contact size 20
Material of -insulator:	green polyester class UL 94 V-0
-shell:	Steel
-contact:	brass
Plating of -shell:	cadmium-lead
-contact:	
mating area;	AU 0.4 μ mini
termination area;	5n Pb 2 μ mini
Contact diameter:	1 mm
cable diameter:	AWG 20 maxi (0.6mm ²)
Temperature range:	-55°C,+125°C
Salt spray :	-48 hours
Damp heat :	-56 days

Part number		DBMF17W2PN	
a	05/06/02	Creation of drawing.	--
ISS	DATE	Latest modification by : JOUBERT	MOD N°
Designed by: JOUBERT date 05/06/02		Type of drawing:	CLIENT
TITLE : PIN MARK I CONNECTOR 2 COAX 15 SOLDER CTS WITH FLOAT MOUNTING			SHEET 1/1
SCALE:	2		
		FRAMATOME CONNECTORS FRANCE Rue Louis Breguet - BP 05 72024 LE MANS Cedex Tel. 33 (16) 43.84.08.43	This document is the property of FRAMATOME CONNECTORS FRANCE It must not be reproduced or communicated without permission in writing from the owners
FORMAT	A3	SOURIAU DRG N° C01-8639-1975	PROJECT M94D001