



CHARACTERISTICS:

Max current rating:	7.5A per standard contact
Dielectric withstanding voltage:	1000V minimum
Insulation resistance:	>5000Ma
Contact resistance:	<7.3ma
Mating and unmating forces:	conform to MILC24308
Contact retention:	40N for contact size 20
Material of -insulator:	green polyester class UL 94 V-0
-shell:	Steel
-contact:	brass
Plating of -shell:	cadmium lead
-contact:	
mating area:	Ni 0.8µmini + Au0.4µmini
termination area:	Ni 0.8µmini + Sn Pb 2µmini
Contact diameter:	1 mm
Temperature range:	-55°C,+125°C

PART NUMBER: DCM21WA4S500N

a	23/10/96	Creation of drawing	--
ISS	DATE	Lastest modification by : JOUBERT	MOD N°
Designed by: JOUBERT date:23/10/96		Type of drawing: CUSTOMER	
Checked by : FONTENEAU date: --		Released by: --	
TITLE : SOCKET CONNECTOR SUB D RIGHT ANGLED SPILL WITH PLASTIC BRACKET			
SCALE	Special mfg:--	MATERIAL:--	N°: --
1.5	item list n°: --	--	--
	General Linear Tolerances: --	General machining surface texture: -- <input checked="" type="checkbox"/>	Geometrical Tolerances see NF E 04-552
	FRAMATOME CONNECTORS FRANCE Rue Louis Breguet - BP 05 72024 LE MANS Cedex Tel. 33 (16) 43.84.08.43		SHEET 1/1
	This document is the property of FRAMATOME CONNECTORS FRANCE It must not be reproduced or communicated without permission in writing Flow the owners		
FORMAT A3	SOURIAU DRG N° C01-8639-0649		PROJECT M94D001