

LAYOUT DIMENSIONS
CONNECTOR SIDE VIEW

TECHNICAL CHARACTERISTICS

- Insulator thermoplastic
- Shell steel cadmium plated


ELECTRICAL DATA

- I maxi 7.5 A signal contact
- Contact resistance $\leq 7.3\text{m}\Omega$
- Insulation resistance $> 5000\text{M}\Omega$
- TEST VOLTAGE
- contact/contact $> 1000\text{V}$
- contact/ground $> 1200\text{V}$

- Finish on contact area: $0.4\ \mu$ gold over nickel
- Finish on terminaison end : bright tin lead over nickel

ENVIRONMENTAL DATA

- Climatic category -55° C/125° C/56j
- Corrosion salt spray: 48h



Part Number		DCM27W2P300N	
a	05/07/00	First issue.	--
ISS	DATE	Latest modification by :	--
Designed by: LELEON		date: 05/07/00	Type of drawing: CLIENT
TITLE : PIN CONNECTOR WITH STRAIGHT CONTACT			SHEET 1/1
SCALE: 2	FRAMATOME CONNECTORS FRANCE Rue Louis Breguet - BP 05 72024 LE MANS Cedex Tel. (33)02.43.78.34.00		This document is the property of FRAMATOME CONNECTORS FRANCE. It must not be reproduced or communicated without permission in writing from the owners.
FORMAT A3	DRG N° C01-8639-1735	PROJECT M94D001	