



CHARACTERISTICS:

Dielectric withstanding voltage: 1000V minimum
 Insulation resistance: >5000MΩ
 Material of -insulator: green thermoset (diallylphthalate)
 -shell: steel
 Plating of -shell: cadmiun
 Temperature range: -55°C,+125°C

TEST RESULTS

Results of salt spray test: method 1001 of MIL STD 1344
 Shock test results: method 2004 MIL STD 1344 discontinuity ≤1 microsecond
 Vibrations: method 2005 of MIL STD 1344 discontinuity ≤1 microsecond
 Humidity: method 1002 of MIL-STD-1344

part number : DCM8W8SN

a	13/07/95	creation of drawing		--
ISS	DATE	Lastest modification by : --		MOD N°
Designed by: JARRY date:13/07/95		Type of drawing: CLIENT		
Checked by : FONTENEAU date:13/07/95		Released by: -- --		
TITLE : SOCKET CONNECTORS FOR EIGHT CONTACTS				
SCALE	Special mfg:--	MATERIAL:--	N°: --	
1.5	item list n°: --	--		
	General Linear Tolerances: --	General machining surface texture: -- <input checked="" type="checkbox"/>	Geometrical Tolerances see NF E 04-552	SHEET 1/1
			FRAMATOME CONNECTORS FRANCE Rue Louis Breguet - BP 05 72024 LE MANS Cedex Tel. 33 (16) 43.84.08.43	
FORMAT A3		SOURIAU DRG N° C01-8639-0586		PROJECT M94D001