



--
DCMF21WA4SN
Part number

CHARACTERISTICS:

Dielectric withstanding voltage: 1000V minimum
 Insulation resistance: >5000Ma
 Contact resistance: <7.3ma
 Mating and unmating forces: conform to MILC24308

Contact retention: 40N for contact size 20
 Material of -insulator: green polyester class UL 94 V-0
 -shell: Steel
 -contact: brass

Plating of -shell: Cadmium
 -contact: AU 0.4µ mini
 mating area: Sn Pb 2 µ mini
 termination area:
 Temperature range: -55°C,+125°C

a	30/09/02	creation of drawing .	--
ISS	DATE	Latest modification by : JOUBERT	MOD N°
Designed by: JOUBERT date 30/09/02		Type of drawing: CLIENT	SHEET 01
TITLE : MALE CONNECTOR 21WA4 WITH ACCESSORIES			
SCALE: 1.5		FRAMATOME CONNECTORS FRANCE Rue Louis Breguet - BP 05 72024 LE MANS Cedex Tel. 33 (16) 43.84.08.43	This document is the property of FRAMATOME CONNECTORS FRANCE It must not be reproduced or communicated without permission in writing from the owners
FORMAT	SOURIAU DRG N°		PROJECT
A3	C01-8639-2000		M94D001