



**ELECTRICAL DATA**

- Max current standard contacts: 7.5A per contact
- Contact resistance  $\leq 7.3m\Omega$
- Insulation resistance  $\geq 5000M\Omega$
- TEST VOLTAGE
  - contact/contact  $\geq 1000V$
  - contact/ground  $\geq 1200V$
- Finish on contact area:  $0.4 \mu$  gold over nickel
- Finish on terminaison end : bright tin lead over nickel

**ENVIRONMENTAL DATA**

- Climatic category -55° C/125° C/56j
- Corrosion salt spray: 48h

PART NUMBER	DDM24W7SN
-------------	-----------

a	27/04/01	Creation of drawing	--
ISS	DATE	Latest modification by :	MOD N°
Designed by: JARRY		date: 27/04/01	Type of drawing: CLIENT
TITLE : SOCKET CONNECTOR 24W7 WITH SOLDERS CONTACTS			SHEET 1/1
SCALE: 2			
		FRAMATOME CONNECTORS FRANCE Rue Louis Breguet - BP 05 72024 LE MANS Cedex Tel. (33)02.43.78.34.00	This document is the property of FRAMATOME CONNECTORS FRANCE It must not be reproduced or communicated without permission in writing from the owners
FORMAT <b>A3</b>	DRG N° <b>C01-8639-1888</b>	PROJECT <b>M94D001</b>	

