



**NOTES:-**

- THE "LF" PRODUCTS MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
- THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 3.5 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.6 MM MINIMUM THICK CIRCUIT BOARD
- LEAD FREE OR RoHS DIRECTIVE LABELING TO BE PROVIDED AS PER GS-14-920 FOR LEAD FREE VERSION.

mat'l. code		surface		tolerance		projection		product family			
-		ISO 1302 ✓		ISO 406 ISO 1101				8609			
ltr		ecn no		dr		date		tolerances unless otherwise specified		title	
A		I04-0100		MINI		09/11/2004		angles		DIN STANDARD RECEPTACLE	
B		I05-0089		MINI		19/05/2005		linear		STRAIGHT SPILL DIN 41612 STYLE-B/2	
C		I06-0062		MINI		01/06/2006		0°±1'		scale -	
				dr		MINI K VANDANATH 23/09/2004				dwg no	
				enfr		RAKHEE GEORGE 23/09/2004				sheet 1 of 1 size	
				chr		RAKHEE GEORGE 01/06/2006				A3	
				appd		RAKHEE GEORGE 01/06/2006				type Product Customer Drawing	
sheet index		revision		C							
		sheet		1							