



- △ HOUSING MATERIAL: GLASS-FILLED POLYESTER. COLOR: POST MATERIAL, PHOSPHOR BRONZE.
- △ POST FINISH: DIN 41612 CLASS 3 IN CONTACT AREA. TIN-LEAD PLATE ON POSTS.
- △ POST FINISH: DIN 41612 CLASS 2 IN CONTACT AREA. TIN-LEAD PLATE ON POSTS.
- △ ACTION PIN POSTS REQUIRE 2.36[0.093] MINIMUM THICK PC BOARD. RECOMMENDED PC BOARD HOLES ARE 1.151[C 0.008].00031 MINIMUM TIN-LEAD PLATING. FINISHED AFTER PLATING. 0.94-1.09[0.037-0.043] DIA.
- △ [PART NUMBER, DATE CODE] MARKED THIS APPROXIMATE A MARKING ON THIS SIDE.

OBsolete	1-16	X	-	X	32
△	1-16	X	-	X	32

NOTES	POSITIONS LOADED	ROWS LOADED	NO. OF ASSY POSITION
	C	B A	

DO NOT SCALE PRINT. DIMENSIONS SPECIFIED IN MILLIMETERS (DIMENSIONS IN INCHES) TOLERANCES ON 1 PLCS DEC ± 0.13(.005) 2 PLCS DEC ± 0.13(.005) ANGLES MATERIAL HOUSING: △ POST: △	DR L. BRINER 3/18/91	NAME
UNLESS SPECIFIED DIMENSIONS TOLERANCES ON 1 PLCS DEC ± 0.13(.005) 2 PLCS DEC ± 0.13(.005) ANGLES MATERIAL HOUSING: △ POST: △	CHK D.C. RUBENDALL 3/26/91	AMP
	APPD D.C. RUBENDALL 3/26/91	AMP Incorporate
	APPD K.R. PARKER 3/26/91	Harrisburg, PA
	PRODUCT SPEC	
FINISH POST: △	APPLICATOR SPEC	PIN ASSEMBLY, EURO
	SIZE	TYPE "1/2R"
	SCALE	