



1. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
2. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.6mm THICK CIRCUIT BOARD.

PT. NO.	PARTS NAME	MATERIAL	Q'TY	NOTE
1	HOUSING	PBT RESIN GLASS REINFORCED (UL94V-0)	1	COLOR : BLACK
2	SLIDER		1	
3	CONTACT	PHOSPHOR BRONZE	n	PLATING : Sn Ni UNDER PLATED (LEAD FREE)

n : NO. OF CONTACTS

mat'l. code				surface ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection	product family 58KF	CODE JP
ltr	ecn no	dr	date	tolerances unless otherwise specified		mm	title 1.25mm SPACING FPC/FFC CONNECTOR (Cat. No. SLD__S-2LF)	
A	J05-0435	H.T	7/8/05	angles	linear ±0.3			
B	J05-0733	H.T	10/28/05					
C	J06-0503	H.T	11/28/06			scale	dwg no sheet 1 of 1 size	
				dr	<i>H. Hoshino</i>	<i>11/28/06</i>	JSA 96552 A4	
				enr	<i>H. Hoshino</i>	<i>11/28/06</i>		
				chr	<i>R. Zhou</i>	<i>11/28/06</i>		
				app	<i>S. Oudani</i>	<i>11/28/06</i>		
sheet index	revision	C	1			type Product Customer Drawing		Rev. C