



1. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
2. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.6mm THICK CIRCUIT BOARD.

PT. NO.	PARTS NAME	MATERIAL	Q'TY	NOTE
1	HOUSING	PBT RESIN GLASS REINFORCED (UL94V-0)	1	COLOR : BLACK
2	SLIDER		1	
3	CONTACT	PHOSPHOR BRONZE	n	PLATING : Sn Ni UNDER PLATED (LEAD FREE)

n : NO. OF CONTACTS

mat'l. code				surface 58 / tolerance ISO 1302 / ISO 406 / ISO 1101	projection	product family 58KF	CODE JP	
ltr	ecn no	dr	date	tolerances unless otherwise specified	mm	title 1.25mm SPACING FPC/FFC CONNECTOR (Cat. No. SLD__S-1LF)		
A	J05-0435	H.T	7/8/'05	angles linear ±0.3				
B	J05-0733	H.T	10/28/'05					
C	J06-0503	H.T	11/28/'06		scale X			
				dr	FCI	dwg no sheet 1 of 1 size		
				enr		JSA 96550 A4		
				chr		type Product Customer Drawing		
				app				
sheet index	revision sheet	C	1					Rev. C