


NOTES

1. Material: SS 7030 (Zamak 5)
2. Packaging see GS-14-639
3. Surface treatment tin electroplating: min. 4 micron Cu, min. 6 micron Ni, 1: min. 6 micron Sn Bright + passivation.

4-ROHS INFORMATIONS:

- This product meets European Union Directives and other country regulations as described in GS-22-008.
- Packaging spec: see GS-14-920.



| | | | | |
|--------------------|------------|-------------------------|-----------------------------------|-------------------|
| www.fciconnect.com | | surface ISO 1302 | tolerance std ISO 406 ISO 1101 | projection mm |
| | | ANGULAR | 0.X ±0.3 | size A2 Scale 1:1 |
| | | LINEAR | 0.XX ±0.1 | ECN LS08-0024 |
| | | Product family | 0.XXX ±0.05 | Spec ref RELEASED |
| Dr J. TARON | 15/12/04 | SOFIX | | Rev. D |
| Eng J. TARON | 2004/12/15 | 72 POS. SHIELDING COVER | | 10009609_C |
| Chr P. LEGARE | 2004/12/15 | 10009609-002 | | sheet 1 of 1 |
| Appr P. LEGARE | 2004/12/15 | CUSTOMER | | |

| rev | acc no | dr | date |
|-----|-----------|-----|------------|
| A | LS4129 | - | - |
| B | LS06-0084 | LGO | 2006/06/22 |
| C | LS07-0001 | MPE | 2007/01/04 |
| D | LS08-0024 | LGO | 2008/01/23 |
| - | - | - | - |
| - | - | - | - |
| - | - | - | - |