



- △ ZINC.
- △ STAINLESS STEEL.
- 3. TO ASSEMBLE JACKSCREW REFER TO INSTRUCTION SHEET #1189.
- △ HOLE CENTRALLY LOCATED WITHIN ±0.07 [.003] OF THE 5.54 [.218] DIA AND THE 2.77/2.84 [.109/.112] DIA CENTER LINES.
- △ CHROMATE CONVERSION, CLEAR WITH HEXAVALENT CHROMATE.
- △ CHROMATE CONVERSION, CLEAR W/O HEXAVALENT CHROMATE.

OBSELETE	△	2.87 [.113]	201910-5
	-	2.11 [.083]	201910-3
	△	2.87 [.113]	201910-1
NOTES	A		PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K. FOLTZ 05/26/94	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm [INCHES]		CHK R. STONE 06/16/94	APVD	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME		
0 PLC ± -		PRODUCT SPEC		
1 PLC ± -		APPLICATION SPEC		
2 PLC ± 0.13 [.005]		SIZE		
3 PLC ± -		CAGE CODE		
4 PLC ± -		DRAWING NO		
ANGLES ± -		RESTRICTED TO		
MATERIAL		WEIGHT		
JACKSCREW BODY: △		A1 00779 ©=201910		
JACKSCREW TIP: △		CUSTOMER DRAWING		
JACKSCREW PIN: △		FINISH JACKSCREW BODY: SEE NOTES		
		JACKSCREW PIN: PASSIVATE		
		SCALE 4:1 SHEET 1 OF 1 REV L1		