



- ⚠ ZINC.
- ⚠ STAINLESS STEEL.
- 3. TO ASSEMBLE JACKSCREW REFER TO INSTRUCTION SHEET #1189.
- ⚠ HOLE CENTRALLY LOCATED WITHIN ± 0.07 [.003] OF THE 5.54 [.218] DIA AND THE 2.77/2.84 [.109/.112] DIA CENTER LINES.
- ⚠ CHROMATE CONVERSION, CLEAR WITH HEXAVALENT CHROMATE.
- ⚠ CHROMATE CONVERSION, CLEAR W/O HEXAVALENT CHROMATE.

⚠	201911-5
⚠	201911-1
NOTES	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K.FOLTZ 05/26/94	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm [INCHES]		CHK R.STONE 06/16/94	APVD	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME		
0 PLC ± -		PRODUCT SPEC		
1 PLC ± -		APPLICATION SPEC		
2 PLC ± 0.13 [.005]		SIZE		
3 PLC ± -		CAGE CODE		
4 PLC ± -		DRAWING NO		
ANGLES ± -		RESTRICTED TO		
MATERIAL JACKSCREW BODY: ⚠ JACKSCREW TIP: ⚠ JACKSCREW PIN: ⚠		FINISH JACKSCREW BODY: SEE NOTES JACKSCREW PIN: PASSIVATED		WEIGHT
		A1 00779 C=201911		
		CUSTOMER DRAWING		SCALE 4:1 SHEET 1 OF 1 REV J1