



THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION		DATE	DWN	APVD	
FT	0	L	REVISED PER ECO-07-010234	5/2/07	SS	GS	



DIM A ±.015 WHEN FULLY SEATED



- MATES WITH 205608 HOUSING.
- CONTACTS ARE AUTOMATICALLY WIREABE.
- FOR PANEL CUT OUT SEE DWG. 205607 CUSTOMER.
- POST LENGTH WILL ACCEPT 3 TERMINATIONS.
- THE MAX. WIRE TO BE USED WITH THIS CONNECTOR IS NO. 24 AWG.
- GOLD PER MIL-G-45204 OVER NICKEL PER QQ-N-290.
- POSTS PLATED TIN-LEAD PER MIL-T-10727 OVER NICKEL PER QQ-N-290.
- POSTS PLATED TIN PER MIL-T-10727 OVER NICKEL PER QQ-N-290.

POST FINISH	DIM B	DIM A	PART NUMBER
8	.017	.215	205628-5
7	.017	.215	205628-3
7	.000	.810	205628-2
6	.000	.810	205628-1

OBSOLETE

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S SCHLEGEL 4/6/05	tyco Tyco Electronics Corporation	
DIMENSIONS: INCHES		CHK G STEINHAEUER 4/6/05	Harrisburg, Pa 17105-3608	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD G STEINHAEUER 4/6/05	NAME BLOCK ASSEMBLY, PIN, 15 POSN, AUTOWIRE POST, .200 GRID	
0 PLC ± -		PRODUCT SPEC -	SIZE A2	CAGE CODE 00779
1 PLC ± -		APPLICATION SPEC -	DRAWING NO C=205628	RESTRICTED TO -
2 PLC ± .02		WEIGHT -	SCALE 4:1	SHEET 1 OF 1
3 PLC ± .005		CUSTOMER DRAWING	REV L	
4 PLC ± -				
ANGLES ± 0°30'				
FINISH -				