



RECOMMENDED PC BOARD LAYOUT

RECOMMENDED PANEL CUTOUT  
 SCALE 1:1

1.75 [.069]	32.36 [1.274]	1.40-1.98 [.055-.078]
2.74 [.108]	30.05 [1.183]	0.79-1.40 [.031-.055]
B	A	PANEL THICKNESS

- 1 PANEL CUTOUT FOR REAR MOUNTED PIN BLOCK.
- 2 SEAMS OF ALL PINS TO BE ORIENTED TOWARD HOLE X SIDE.
- 3 POLYESTER, BLACK.
- 4 0.76um [.000030] MIN GOLD PER MIL-G-45204 FOR A LENGTH OF 6.35 [.250] MIN FROM MATING END, GOLD FLASH ON REMAINDER, BOTH OVER 1.27um [.000050] MIN NICKEL PER QQ-N-290.
- 5 2.54um [.000100] MIN TIN-LEAD PER MIL-T-10727 OVER 2.54um [.000100] MIN COPPER PER MIL-C-14550.
- 6 2.54um [.000100] MIN TIN PER MIL-T-10727 OVER 2.54um [.000100] MIN COPPER PER MIL-C-14550.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWG L.SIPE 09/09/92	Tyco Electronics Corporation Harrisburg, Pa 17105-3608	
DIMENSIONS: mm [INCHES]		CHK R.STONE 10-15-92	APVD	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME		
0 PLC ± -	1 PLC ± -	PRODUCT SPEC		
2 PLC ± 0.13 [.005]	3 PLC ± 0.013 [.0005]	APPLICATION SPEC		
4 PLC ± -	ANGLES ± -	SIZE CAGE CODE DRAWING NO		
MATERIAL FINISH		WEIGHT	A1 00779 C=211580	RESTRICTED TO
		CUSTOMER DRAWING		SCALE 2:1 SHEET 1 OF 1 REV N