



- NOTES:**
- MATERIAL: THERMO PLASTIC POLYESTER; 30 % GF, UL-94-v0; COLOUR: GREY
 - DIFFERENTS TYPES HOLES:
 - TYPE 1: FOR RETENTION Ø0.68 ON ROWS "a" AND "c" ON CAVITIES 1 TO 6, 15 TO 18 AND 27 TO 32
 - TYPE 2: Ø0.75 ON OTHER HOLES ON ROWS "a" AND "c"
 - TYPE 3: Ø0.85 ON HOLES ON ROW "b"
 - RETENTION OF CONNECTOR WITH ROWS "a" AND "c" ; FULLY LOADED 180N MIN
 - THE "LF" PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
 - LEADFREE OR RoHS DIRECTIVE LABELLING TO BE PROVIDED AS PER GS-14-920.
 - " LF " SUFFIX TO PRODUCT NUMBER FOR RoHS COMPATIBLE/ LEADFREE VERSION.
 - PARTS WITH AND WITHOUT "LF" SUFFIX ARE FORM-FIT AND FUNCTIONALLY IDENTICAL.
" LF " SUFFIX PROVIDED FOR PART NUMBER STANDARDISATION OF PART THAT MEETS RoHS REQUIREMENTS.

PRODUCT NUMBER
70017-001

mat'l. code		surface		tolerance		projection		product family	
SEE NOTES		ISO 1302 ✓		ISO 406 ISO 1101		mm		BACKPANEL	
tolerances unless otherwise specified		angles		linear		scale 2:1		title	
ltr	ecn no	dr	date					B.P. SHROUD HIGH RETENTION	
D	F50459	OMA	1995-06-20					dwg no	
E	F50955	OMA	1995-12-20					sheet 1 of 1 size	
F	I06-0082	MINI	2006-06-01					70017 A3	
		dr		O.MATHEWON		1995-05-03		type	
		enrg		M.MEUNIER		1995-05-03		Product Customer Drawing	
		chr		RAKHEE GEORGE		2006-06-01			
		appd		RAKHEE GEORGE		2006-06-01			
sheet index	revision sheet	F	1						



Copyright FCI