



**PERFORMANCE CHARACTERISTICS**

CURRENT RATING: 1.5 A AT 20°C (FULLY LOADED)  
1 A AT 70°C (FULLY LOADED)

RATED VOLTAGE: 500 V AC (CONT /CONT)  
OPERATING TEMPERATURE : -55°C TO 125°C  
CONTACT RESISTANCE : 20 mΩ MAX  
INSERTION FORCE : 0.75N MAX/CONT  
EXTRACTION FORCE : 0.15N MIN /CONT  
INSULATION RESISTANCE: 10<sup>4</sup>MΩ MIN

**NOTES**

- LEAD FREE INDICATOR :LF-LEAD FREE  
PERFORMANCE LEVEL INDICATOR (REF DWG NO.BS.C.201844.003)
- THIS PRODUCT IS CSA APPROVED.  
THIS PRODUCT IS UL RECOGNIZED.
- FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING :BS.A.201572.001
- THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

Material		Spec ref	
Mat code	tolerance	projection	MM
Heatreat	✓ IDEC ±0.2 IDEC 2DEC ±0.1 2DEC ANGLES ±1°HOEKEN		
Plating/Finish		size	Scale
Dr 24 9 96	W.Panis	AI	5.000
Eng	Product family MILLIPACS	ECN	
Chr	Model Name	REL Level	
Appr	Model Revision		
	WILLIPACS 2 LOADING PATTERN RIGHT ANGLE FEMALE	dwg no BSC202468002	Rev. B

rev	ecn no	dr	date
A	CONVERSION REVISION 00	KN	14-9-01
B	DG05-0278	Kaso	02-08-05
-	-	-	-
-	-	-	-
-	-	-	-