

HC-A 4-EBUS

Order No.: 1774908

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1774908>

HEAVYCON female insert, A4 series, 4-pos., screw connection

Commercial data

EAN	4017918122256
Pack	10 Pcs.
Customs tariff	85366990
Weight/Piece	0.01969 KG
Catalog page information	Page 341 (PC-2007)

Product notes

WEEE/RoHS-compliant since:
01/31/2006

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Note	For housing HC-D7
Connection systems	Screw connection
Tightening torque	0.25 Nm
Ambient temperature (operation)	-40 °C ... 125 °C (including heating up of contacts)
Pollution degree	3

Surge voltage category	III
Test voltage	4 kV AC
Constructional and testing regulations	DIN VDE 0627/86
	DIN VDE 0110/02.79
	DIN VDE 0110-1/04.97
	IEC 60664-1, DIN IEC 60512
	IEC 60352
Number of positions	4
Insertion/withdrawal cycles	≥ 500
Design	A4
Connection in acc. with standard	IEC / EN
Conductor cross section	0.5 mm ² ... 1.5 mm ²
Connection cross section AWG	20 ... 16
Stripping length of the individual wire	5 mm

Material data

Inflammability class acc. to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PA

Electrical characteristics

Rated voltage (III/3)	230 V (Conductor-PE)
	400 V (Conductor-Conductor)
Rated surge voltage	4 kV
Rated current	10 A

Certificates / Approvals

Approval logo



CSA


Nominal voltage U _N	600 V
Nominal current I _N	10 A

UL


AWG/kcmil	20-13
Certification	CSA, GOST, UL

Drawings

Diagram




Dimensioned drawing



Female insert

Schematic diagram



Address

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2008 Phoenix Contact
Technical modifications reserved;