



A1RFRD10

REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	CHKD
△		ADD P/N	JAWY 12/10/05	



PC Board Layout Component Side Shown
Thickness=1.6mm

ROHS PART NUMBER: E5908-XVCXXX-L

1- 3u" 2- 6u" 3-15u"
4-30u" 5-50u"

- 2-W/ TOP TABS
- 3-W/ SIDE TABS
- 4-W/ TOP&SIDE TABS
- 5-W/ TOP&BOTTOM&SIDE TABS

- 14-FRONT 4.57 W/O LOGO △
- 1J-FRONT 4.57 W/FRE LOGO W/O UL LOGO

NOTES:
ELECTRICAL:

1. VOLTAGE RATING : 125 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 50 MILLIOHMS MAX.
4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
5. DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.

MECHANICAL:

1. HOUSING&PIN'S& MATERIAL : PBT+30%.G.F BK UL94V-0.
2. CONTACT MATERIAL : PHOSPHOR BRONZE, t=0.35mm.
3. SHIELD MATERIAL : COPPER ALLOY, t=0.25mm.
4. PLATING : GOLD PLATING OVER NICKEL.
5. OPERATING LIFE : 750 CYCLES MIN.
6. PCB RETENTION PRE-SOLDER : 1 LB MIN.
7. PCB RETENTION POST-SOLDER: 10 LBS MIN.

ENVIRONMENTAL:

1. STORAGE : -40°C TO +85°C.
2. OPERATION: -0°C TO 70°C.
3. WAVE SOLDERING TEMPERATURE: 230°C ~250°C (3~5 SECONDS).

MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.
CUL FILE NO. E163191

DETACHED LISTS	MM (INCH)	DFTO CY	DATE 06/11/05	FULL RISE ELECTRONIC CO., LTD	
	TOLERANCES EXCEPT AS NOTED	CHKD WCM	DATE 2006/12/12		
	MFO	DATE			
	APPV/Lus/mg	DATE 2005/12/12			
MM	±	MATERIAL :	TITLE STAMPED PIN III STACKED GANGED JACK, 2X4		
.0 ±0.2	±	QT'Y :			
.00 ±0.15	±	FINISH :	DRAWING NO. GE593B51-LC		SIZE A3
.000 ±0.075	±	SCALE : 1.5 : 1	/PART NO. SEE NOTE		REV 1
ANGLES ± 0.5	THIRD ANGLE PROJECTION	DO NOT SCALE DRAWING		SHEET 1 OF 1	