



NOTES:

ELECTRICAL:

1. VOLTAGE RATING : 125 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 35 MILLIOHMS MAX.
4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
5. DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.

MECHANICAL:

1. HOUSING MATERIAL : GLASS FILLED NYLON UL94V-0.
2. CONTACT MATERIAL : PHOSPHOR BRONZE ϕ 0.46mm
3. CONTACT PLATING : GOLD PLATING OVER NICKLE
4. SHIELD PLATING : NICKEL PLATING OVER BRASS
5. OPERATING LIFE : 750 CYCLES MIN.
6. PCB RETENTION PRE-SOLDER: 1 LB MIN.
7. PCB RETENTION POST-SOLDER: 10 LBS MIN.
8. LED COLOR : LEFT- GREEN, RIGHT- YELLOW.

ENVIRONMENTAL:

1. STORAGE TEMPERATURE : -40°C TO +85°C.
2. OPERATION TEMPERATURE: -40°C TO +85°C.
3. WAVE SOLDERING TEMPERATURE: 255~265*(5~10 SECONDS)
4. RoHS COMPLIANT.

MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

| |
|----------------|
| PART NUMBER |
| E5J88-C4B3F2-L |

| | | | | | |
|--|--|---|--|--|--|
| | | RoHS Compliant | | | |
| TOLERANCES EXCEPT AS NOTED MM .0 ± 0.2 ± .00 ± 0.15 ± .000 ± 0.075 ± | | TITLE STACKED GANGED JACK 2*3 PORTS | | | |
| ANGLES ± 0.5 | | DFTO Cathy DATE 2006/09/11 | | DRAWING NO. CE5J3035-LA /PART NO. SEE TABLE | |
| DETACHED LISTS | | SCALE : 5:3 | | SIZE REV A3 0 | |
| THIRD ANGLE PROJECTION | | DO NOT SCALE DRAWING | | SHEET 1 OF 1 | |