




REVISION							
REV.	DESCRIPTION	DATE	APPROVED				
В	RoHS Compliancy	06-01-06	DP				
С	UL Reapproval	05-27-07	DP				

THESE DRAWINGS ARE THE PROPERTY OF QUALTEK ELECTRONICS AND NOT TO BE REPRODUCED FOR OR COMMUNICATED TO A THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF AN OFFICER OF QUALTEK ELECTRONICS.






PANEL CUTOUT



R1



120-250

250-500

0.90

1.20

R.Nuti

05-27-07

## NOTES:

USE 12 AWG SOLID COPPER WIRE ONLY 20A 125V PANEL THICKNESS: 0.8~1.8mm APPROVALS: UL, cUL PRODUCT SHIPPED UNASSEMBLED **RoHS COMPLIANT** 

## Cover back of the body NYLON Black Color

## **CONTROLLED**

JJH / 05-27-07

5	Cover back of the body, NYLON Black Color					
4	Contact PIN Bronze Strip t=0.7mm					1
З	Contact PIN Bronze Strip t=0.7mm					
2	Contact PIN Bronze Strip t=0.7mm Ni-Plated					
1	Body li	Body Insulator NYLON Black Color				
Dim range (mm)		Tolerance +/-	Qualtek Electronics Corp. PPC DIVISION			
		(mm)	Part Number: 7	'39W-X2/20	RoHS Compliant	
0-1		0.15	Description: SNAP-IN 20 AMP T-SLOT RECEPTACLE			
1-6 0.20 SNA		AP-IIN ZU AIVIP T-SLUT RECEPTACLE				
	6-18	0.30				
1	8-50	0.50		UNIT: mm	REV. C	
5	0-120	0.70	Drawn / Date	Checked / Date	Approved / Date	

05-27-07