

## Model 72973 SMA JACK (F) TO JACK (F), PANEL



Model 72973 SMA JACK (F) TO JACK (F), PANEL

# High bandwidth, small size, and durability for confident connections

#### **Features**

- DC 18 GHz
- Meets MIL-C-39012, IEC 169-15, CECC 22110.
- Small size and durability for mobile communications.
- Precision machined and gold-plated for low loss.

#### **Materials**

- Body is machined brass with gold plating.
- Center Contacts Plug is gold plated brass and Jack is gold plated Beryllium copper.
- Insulators are high quality PTFE.
- Crimp Ferrules are copper with gold or nickel plating.
- · Gaskets are silicone rubber.

## **Ordering Information**

Model: 72973

Description: SMA JACK (F) TO JACK (F), PANEL


**USA:** Sales: 800-490-2361

Technical Support: <a href="mailto:technicalsupport@pomonatest.com">technicalsupport@pomonatest.com</a>

Fax: 425-446-5844

**Europe:** 31-(0) 40 2675 150 **International**: 425-446-5500

Where to Buy: www.pomonaelectronics.com



### **Specifications**

| <u> </u>                           |  |
|------------------------------------|--|
| 50 Ω                               |  |
| DC –18 GHz max.                    |  |
| < 500 Vpeak                        |  |
| 1,000 Vrms                         |  |
| 1.25 max.                          |  |
| 0.003/0.002 Ω max                  |  |
| > 5000 MΩ                          |  |
| 500 cycles minimum                 |  |
| -65° C to 165° C, -85° F to 329° F |  |
|                                    |  |

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02$ " (.51 mm),  $.xxx = \pm .005$ " (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

D2003384 REV 001