


REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₂	REVISED	08/04/94	<i>AD</i>

HOUSING (OSB)	BRASS PER ASTM-B-16 HALF HARD	NICKEL PLATE PER QQ-N-290
HOUSING (OSM) COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
COMPONENT	MATERIAL	FINISH

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions	Temperature Rating <u>-65°C to +125°C</u>
Frequency Range (GHz) <u>DC to 4</u>	BNC <u>MIL-STD-348A Fig. 301.2</u>	Vibration <u>MIL-STD-202, Method 204, Condition D</u>
Volt Rating (VRMS MAX) <u>Sea Level 335</u>	OSM <u>MIL-STD-348A Fig. 310.1</u>	Shock <u>MIL-STD-202, Method 213, Condition I</u>
VSWR <u>1.30 Max at 0.5 to 4.0 GHz</u>	Recommended Mating Torque <u>4-6 In-Lbs</u>	Thermal Shock <u>MIL-STD-202, Method 107, Condition C,</u>
Insertion Loss (dB MAX) <u>0.2√f(GHz)</u>	Mating Characteristics:	Moisture Resistance <u>MIL-STD-202, Method 106</u>
RF Leakage (dB MIN) <u>-55, 2 to 3 GHz</u>		Corrosion - <u>MIL-STD-202, Method 101, Condition B, 5% salt spray</u>
Corona, 70,000 Ft (VRMS MIN) <u>250</u>	Insertion (Lbs Max) <u>2.0</u> <u>N/A</u>	
Dielectric Withstanding Voltage (VRMS MIN) <u>Sea Level 1500</u>	Withdrawal (Oz Min) <u>2.0</u> <u>N/A</u>	
Contact Resistance (Milliohms MAX)	Force to Engage/Disengage	
Center Contact <u>4.1</u>	Longitudinal	
Outer Contact <u>2.2</u>	Force (Lb Max) <u>3.0</u> <u>N/A</u>	
RF High Potential <u>Sea Level (VRMS MIN @ 5 MHz) 670</u>	Torque (In-Lb Max) <u>2.5</u> <u>2.0</u>	
I.R.(Megohms MIN) <u>5000</u>	Contact Retention	
	Axial (Lbs Min) <u>6.0</u>	
	Radial (In-Oz) <u>N/A</u>	
	Weight (Grams) <u>TBD</u>	

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	DRAWN BY <u>DRW</u> DATE <u>6/6/67</u>	 AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
	CHECKED BY <u>KWW</u> DATE <u>6-9-77</u>	
FRAC. DEC. ANGLES	APPD BY <u>RMF</u> DATE <u>6/9/77</u>	
± 1/64 ±.005 ± °	USE ASS'Y PROCEDURE	
These drawings and specifications are the property of M/A-COM Interconnect Division and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of items without written permission.	NO. AP. <u>N/A</u>	
TITLE <u>BNC JACK TO OSM PLUG ADAPTER</u>		
SIZE <u>B</u>	CODE IDENT NO. <u>26805</u>	REV <u>01₂</u>
SCALE <u>4:1</u>	<u>3282-2241-00</u>	SHEET 1 OF 1