



| REVISIONS | | | |
|-----------------|-------------|----------------|----------|
| REV | DESCRIPTION | DATE | APPROVED |
| 01 ₁ | REVISED | KYLE 9-4-97 | 9/19/97 |

| | | |
|----------------|--|-------------------------------|
| HOUSING | STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303 | PASSIVATE PER QQ-P-35 |
| DIELECTRIC | PTFE FLUOROCARBON PER ASTM-D-1457 | N/A |
| CENTER CONTACT | BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H | GOLD PLATE PER MIL-G-45204 |
| COMPONENT | MATERIAL | FINISH |

| | | | |
|--|---------------|----------------|---|
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES | DRAWN BY | DATE | AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599 |
| | CHECKED BY | | |
| | APPD BY | | |
| FRAC. ± 1/64 | DEC. ±.005 | ANGLES ± 1° | |

| | | | |
|---|---------------------|---|-------------------------|
| These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission. | USE ASSY PROCEDURE | TITLE "OSM" JACK TO "SMC" JACK ADAPTER | |
| | NO. A.P. <u>N/A</u> | SIZE B | CODE IDENT NO. 26805 |
| | | SCALE 8:1 | 5080-2240-00 |
| | | | SHEET 1 OF 1 |

VSWR: 1.04 + .007f(GHz)
@ DC-10.0 GHz

.XXX = in
XX.X = mm (REF)