

LOC	DIST	REVISIONS					
DF	X0	P	LTR	DESCRIPTION	DATE	DWN	APVD
			B	REV PER 0G3D-0490-02	11-02	JMK	JL

This diagram shows an exploded view of a mechanical assembly. The components are numbered 1 through 10. The assembly consists of a large housing (1) with a central bore, a smaller sleeve (2) that fits inside the bore, a central shaft (3) with a pointed end, a small washer (4), a larger washer (5), a long cylindrical component (6) with a flange, and a final flange (7). A small pin (8) is shown near the central shaft. A small rectangular component (9) is shown near the large housing. A small circular component (10) is shown near the final flange.

1

○

Diagram illustrating the assembly components and dimensions for a cable connector:

- Dimensions:**
 - Overall length: .755 [19.18]
 - Internal thread diameter: .312 [7.92] HEX
- Components:**
 - INNER SLEEVE
 - CABLE (CUSTOMER SUPPLIED)
 - CLAMP NUT .312 [7.92] HEX
 - HOUSING
 - COUPLING NUT
 - DIELECTRIC CENTER CONTACT GASKET
 - RETAINING RING
- Assembly Note:** A warning symbol (triangle with exclamation mark) is shown near the retaining ring, indicating a critical assembly step or caution.

21

E

A

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. KAISER	9/25/02
DIMENSIONS:		CHK J.LIPPERT	11-22-02
INCHES [mm]		APVD J.LIPPERT	11-22-02
		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
		0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .005 [0.13] 4 PLC ± - ANGLES ± -	
MATERIAL	FINISH	PRODUCT SPEC	
SEE TABLE	SEE TABLE	APPLICATION SPEC	
		408-4918	
		WEIGHT	TBD
		CUSTOMER DRAWING	

		Tyco Electronics Corporation Harrisburg, PA 17105	
NAME			
SMA STRAIGHT CABLE PLUG-SOLDER CLAMP ATTACHMENT (M39012/79-3007) CAT E			
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-1050781	—
SCALE		SHEET	REV
5:1		1 OF 1	B