

			DESIGNED FOR USE WITH RG-142/U		REVISIONS																																																												
			CABLE ENTRY DIAMETER MINIMUM		REV	DESCRIPTION	DATE	APPROVED																																																									
			FERRULE .218 HOUSING .121 CONTACT .040		01 ₀	RELEASED	11/20/96																																																										
<table><tr><th>ELECTRICAL</th><th>MECHANICAL</th><th>ENVIRONMENTAL</th></tr><tr><td>Nominal Impedance (Ohms) 50</td><td>Interface Dimensions MIL-STD-348A, Fig. 310-2</td><td>Temperature Rating -65 TO +165°C</td></tr><tr><td>Frequency Range (GHz) DC to 12.4</td><td>Recommended Mating Torque 7-10 IN-LBS</td><td>Vibration MIL-STD-202, Method 204, Condition D</td></tr><tr><td>Volt Rating (VRMS MAX) @ Sea Level 335</td><td>Mating Characteristics:</td><td>Shock MIL-STD-202, Method 213, Condition I</td></tr><tr><td>VSWR 1.15 + 0.01f(GHz)</td><td>Insertion (MAX Lbs) 2</td><td>Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C</td></tr><tr><td>Insertion Loss (dB MAX) .06 √f(GHz)</td><td>Withdrawal (MIN Oz) 1</td><td>Moisture Resistance MIL-STD-202, Method 106</td></tr><tr><td>RF Leakage (dB MIN) -60</td><td>Force to Engage and Disengage (In-Lbs MAX) 2</td><td>Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray</td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN) 250</td><td>Center Contact Captivation</td><td></td></tr><tr><td>Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1,000</td><td>Axial (Lbs) 6</td><td></td></tr><tr><td>Contact Resistance (Milliohms MAX)</td><td>Radial (In-Oz) N/A</td><td></td></tr><tr><td>Center Contact 3.0</td><td>Cable Retention</td><td></td></tr><tr><td>Outer Contact 2.0</td><td>Axial Force (Lbs) 40</td><td></td></tr><tr><td>Cable to Housing .05</td><td>Torque (In-Oz) N/A</td><td></td></tr><tr><td>RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670</td><td>Weight (Grams) TBD</td><td></td></tr><tr><td>I.R.(Megohms MIN) 5,000</td><td></td><td></td></tr></table>			ELECTRICAL	MECHANICAL	ENVIRONMENTAL	Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310-2	Temperature Rating -65 TO +165°C	Frequency Range (GHz) DC to 12.4	Recommended Mating Torque 7-10 IN-LBS	Vibration MIL-STD-202, Method 204, Condition D	Volt Rating (VRMS MAX) @ Sea Level 335	Mating Characteristics:	Shock MIL-STD-202, Method 213, Condition I	VSWR 1.15 + 0.01f(GHz)	Insertion (MAX Lbs) 2	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C	Insertion Loss (dB MAX) .06 √f(GHz)	Withdrawal (MIN Oz) 1	Moisture Resistance MIL-STD-202, Method 106	RF Leakage (dB MIN) -60	Force to Engage and Disengage (In-Lbs MAX) 2	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray	Corona, 70,000 Ft (VRMS MIN) 250	Center Contact Captivation		Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1,000	Axial (Lbs) 6		Contact Resistance (Milliohms MAX)	Radial (In-Oz) N/A		Center Contact 3.0	Cable Retention		Outer Contact 2.0	Axial Force (Lbs) 40		Cable to Housing .05	Torque (In-Oz) N/A		RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670	Weight (Grams) TBD		I.R.(Megohms MIN) 5,000			<table><tr><td>HOUSING MOUNTING NUT LOCKWASHER</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303</td><td>PASSIVATE PER QQ-P-35</td></tr><tr><td>DIELECTRIC</td><td>TFE FLUOROCARBON PER ASTM-D-1457</td><td>N/A</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>O-RING</td><td>SILICONE RUBBER PER ZZ-R-765</td><td>N/A</td></tr><tr><td>FERRULE</td><td>COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM</td><td>GOLD PLATE PER MIL-G-45204</td></tr></table>			HOUSING MOUNTING NUT LOCKWASHER	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35	DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A	CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204	O-RING	SILICONE RUBBER PER ZZ-R-765	N/A	FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204
ELECTRICAL	MECHANICAL	ENVIRONMENTAL																																																															
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310-2	Temperature Rating -65 TO +165°C																																																															
Frequency Range (GHz) DC to 12.4	Recommended Mating Torque 7-10 IN-LBS	Vibration MIL-STD-202, Method 204, Condition D																																																															
Volt Rating (VRMS MAX) @ Sea Level 335	Mating Characteristics:	Shock MIL-STD-202, Method 213, Condition I																																																															
VSWR 1.15 + 0.01f(GHz)	Insertion (MAX Lbs) 2	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C																																																															
Insertion Loss (dB MAX) .06 √f(GHz)	Withdrawal (MIN Oz) 1	Moisture Resistance MIL-STD-202, Method 106																																																															
RF Leakage (dB MIN) -60	Force to Engage and Disengage (In-Lbs MAX) 2	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray																																																															
Corona, 70,000 Ft (VRMS MIN) 250	Center Contact Captivation																																																																
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1,000	Axial (Lbs) 6																																																																
Contact Resistance (Milliohms MAX)	Radial (In-Oz) N/A																																																																
Center Contact 3.0	Cable Retention																																																																
Outer Contact 2.0	Axial Force (Lbs) 40																																																																
Cable to Housing .05	Torque (In-Oz) N/A																																																																
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670	Weight (Grams) TBD																																																																
I.R.(Megohms MIN) 5,000																																																																	
HOUSING MOUNTING NUT LOCKWASHER	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35																																																															
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A																																																															
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204																																																															
O-RING	SILICONE RUBBER PER ZZ-R-765	N/A																																																															
FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204																																																															
<table><tr><th>COMPONENT</th><th>MATERIAL</th><th>FINISH</th></tr><tr><td colspan="3">UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES</td></tr><tr><td>FRAC. ± 1/64</td><td>DEC. ± .005</td><td>ANGLES ± 1°</td></tr><tr><td colspan="3">DRAWN BY K. L. E. DATE 9-26-96</td></tr><tr><td colspan="3">CHECKED BY</td></tr><tr><td colspan="3">APPD BY DATE 11/20/96</td></tr><tr><td colspan="3">USE ASSY PROCEDURE 408-04922 (20-251) NO. A.P.</td></tr><tr><td colspan="3">TITLE "OSM" BULKHEAD FEEDTHRU CABLE JACK CRIMP ATTACHMENT</td></tr><tr><td>SIZE B</td><td>CODE IDENT NO. 26805</td><td>2034-8052-92</td></tr><tr><td>SCALE 5:1</td><td colspan="2">REV 01₀</td></tr><tr><td colspan="2">SHEET 1 OF 1</td><td></td></tr></table>			COMPONENT	MATERIAL	FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			FRAC. ± 1/64	DEC. ± .005	ANGLES ± 1°	DRAWN BY K. L. E. DATE 9-26-96			CHECKED BY			APPD BY DATE 11/20/96			USE ASSY PROCEDURE 408-04922 (20-251) NO. A.P.			TITLE "OSM" BULKHEAD FEEDTHRU CABLE JACK CRIMP ATTACHMENT			SIZE B	CODE IDENT NO. 26805	2034-8052-92	SCALE 5:1	REV 01 ₀		SHEET 1 OF 1																																
COMPONENT	MATERIAL	FINISH																																																															
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES																																																																	
FRAC. ± 1/64	DEC. ± .005	ANGLES ± 1°																																																															
DRAWN BY K. L. E. DATE 9-26-96																																																																	
CHECKED BY																																																																	
APPD BY DATE 11/20/96																																																																	
USE ASSY PROCEDURE 408-04922 (20-251) NO. A.P.																																																																	
TITLE "OSM" BULKHEAD FEEDTHRU CABLE JACK CRIMP ATTACHMENT																																																																	
SIZE B	CODE IDENT NO. 26805	2034-8052-92																																																															
SCALE 5:1	REV 01 ₀																																																																
SHEET 1 OF 1																																																																	