



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
02 ₁	REDRAWN IN CAD PER ECN 98-0001	PATLAN 4-23-98	<i>[Signature]</i> 8/24/1998

RECOMMENDED MOUNTING HOLE

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204
MOUNTING NUT		
LOCKWASHER		
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
CONTACT EXT	IRON-NICKEL-COBALT ALLOY PER MIL-I-23011 CLASS 1 (KOVAR)	GOLD PLATE PER MIL-G-45204
O-RING	SILICONE RUBBER PER ZZ-R-765	N/A
HERMETIC SEAL	GLASS BEAD	N/A

COMPONENT	MATERIAL	FINISH
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY BWC DATE 07-02-68	
FRAC. ± 1/64	CHECKED BY FRB DATE 07-02-68	M/A-COM a Division of AMP Incorporated 140 Fourth Avenue Waltham, MA 02154-7577
DEC. ±.005	APPD BY BWC DATE 02-14-69	
ANGLES ± 1°	USE ASSY PROCEDURE	TITLE HERMETICALLY SEALED STRAIGHT BULKHEAD JACK RECEPTACLE
These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	NO. A.P. N/A	SIZE B
		CODE IDENT NO. 26805
		2056-3100-00
	SCALE 5:1	REV 02 ₁
		SHEET 1 OF 1

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310-2	Temperature Rating -65° TO +165°C
Frequency Range (GHz) DC to 18	Recommended Mating Torque 7-10 IN-LBS	Vibration MIL-STD-1344, Method 2005, Condition IV
Volt Rating (VRMS MAX) @ Sea Level 335	Mating Characteristics:	Shock MIL-STD-1344, Method 2004, Condition G
VSWR 1.05 + .01f(GHz)	Insertion (MAX Lbs) 3.0	Thermal Shock MIL-STD-1344, Method 1003, Condition A, Except High Temp +200°C
Insertion Loss (dB MAX) .04√f(GHz)	Withdrawal (MIN Oz) 1.0	Moisture Resistance MIL-STD-202, Method 106
RF Leakage (dB MIN) -[70-f(GHz)]	Force to Engage and Disengage (In-Lbs MAX) 2.0	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
Corona, 70,000 Ft (VRMS MIN) 250	Center Contact Captivation	
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1,000	Axial (Lbs) 6.0	
Contact Resistance (Milliohms MAX)	Radial (In-Oz) N/A	
Center Contact 7.0	Cable Retention	
Outer Contact 2.0	Axial Force (Lbs) N/A	
Cable to Housing N/A	Torque (In-Oz) N/A	
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670	Weight (Grams) TBD	
LR.(Megohms MIN) 5,000		

.XXX = in
XX.X = mm (REF)