



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
04 ₁	REVISED	6/10/96 6/28/96	<i>RAC</i>

.XXX = in
XX.X = mm

	DIM "A"	DIM "B"
BEFORE CRIMPING	.940 REF	.931 REF
AFTER CRIMPING	.885 MAX	.811 REF
	23.9	23.6
	22.5	20.6

HOUSING COUPLING NUT BUSHING	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
COMPONENT	MATERIAL	FINISH

NOTES:

- DESIGNED FOR USE WITH .141 DIA (RG 402/U) SEMI-RIGID CABLE
- CAPTURED CENTER CONTACT
- PICTORIAL VIEW BEFORE CRIMPING
- MINIMUM STRAIGHT CABLE LENGTH .336
- IT IS SUGGESTED TO BEND CABLE PRIOR TO CRIMPING

CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.1425
CONTACT	.037

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCE ON
FRAC. DEC. ANGLES
± 1/64 ± .005 ± °

These drawings and specifications are the property of M/A-COM Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

DRAWN BY D. CAM	DATE 11/19/82
CHECKED BY R. G.	12/9/82
APPROVED BY R. M. F.	12/13/82

AMP
AMP Incorporated
140 Fourth Avenue
Waltham, MA 02451-7599

USE ASS'Y PROCEDURE
408-04745
(30-085)
NO. AP.

TITLE OSN STRAIGHT CABLE PLUG
SOLDERLESS COMPRESSION
CRIMP ATTACHMENT

SIZE B	CODE IDENT NO. 26805	3001-7641-02	REV 04 ₁
SCALE 4:1			SHEET 1 OF 1