



DESIGNED FOR USE WITH RG180/U	
CABLE ENTRY DIAMETER MINIMUM	
CONTACT	.021
HOUSING	.106
FERRULE	.153

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 <sub>1</sub>	REDRAWN ON CAD ECN 94-0474	6/1/95	<i>RAC</i> 6/1/95

HOUSING COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	GOLD PLATE PER MIL-G-45204
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
SHRINK TUBING	HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/4	N/A
FERRULE	SOFT COPPER ALLOY	GOLD PLATE PER MIL-G-45204

COMPONENT	MATERIAL	FINISH
-----------	----------	--------

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± °	DRAWN BY <b>B.M.</b> 8/17/79	M/A-COM a Division of AMP Incorporated 140 Fourth Avenue Waltham, MA 02154-7577
	CHECKED BY <b>R. SMITH</b> 8/21/79	
	APPD BY <b>G.H.</b> 8/23/79	

These drawings and specifications are the property of M/A-COM Interconnect Division and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE	TITLE OSM STRAIGHT CABLE PLUG SOLDER ATTACHMENT	
	408-04964	SIZE B	CODE IDENT NO. 26805
	NO. AP. 20-080	2031-5156-29	REV 01 <sub>1</sub>

SCALE 5:1 SHEET 1 OF 1