

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AJ	16	F1	REVISED PER ECO-05-013879	28NOV05	BM JGH

1 FOR USE WITH HAND TOOL 220190-1.  
 2 USE WITH MILITARY HAND TOOL M22520/5-01.  
 3 USE WITH MILITARY HAND TOOL M22520/2-01 (DANIELS AFMB) WITH DANIELS POSITIONER K1041.  
 4 SPECIAL XEROX STYLE 1275 CABLE, RG-178/U, -178A/U, -178B/U, -196/U AND -196A/U CABLES.

RECOMMENDED STRIP LENGTH  
SCALE :NTS

ISOMETRIC VIEW

4	SET AT NO 4 POSITION	Y444	58046-1 (AREA A)	414170-2
	RG-174/U, 188/U & 316/U	SET AT NO 4 POSITION	Y444	58046-1 (AREA A)
	FOR USE WITH CABLE	DANIELS POSITIONER CONTACT CRIMP 3	DANIELS DIE SET BRAID CRIMP 2	AMP DIE SET 1
				PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	8-20-91	Tyco Electronics Corporation	
		CHK	9/25/91	Harrisburg, PA 17105-3608	
		APVD	-	NAME	
		PRODUCT SPEC	-	CONNECTOR, JACK, SERIES SMB	
		APPLICATION SPEC	-	SIZE	RESTRICTED TO
		WEIGHT	-	A2	-
		CUSTOMER DRAWING		CAGE CODE	DRAWING NO
				00779	C=414170
				SCALE	SHEET
				8:1	1 of 1
				REV	F1

AMP 1471-9 REV 31MAR2000

414170

B

A