


LOC	DIST	REVISIONS					
AJ	16	P	LTR	DESCRIPTION	DATE	DWN	APVD
		F		SUPERSEDE-22 PER 0E10-0130-99	13DEC99	MO	BM

1. USE WITH: RG-174/U, RG188-U CABLE.



SUGGESTED
PANEL CUT-OUT

OBSOLETE
SUPSD BY 331974
SUPSD BY 2-330060-1

					1-329631-2	JAM NUT	12
					1-329632-2	LOCK WASHER	11
					2-328666-7	FERRULE	10
					2-50793-7	CRIMP END ASSY	9
					2-329803-3	JACK ASSY	8
				1	329633	GASKET	7
				1	329631	JAM NUT	6
				1	329632	LOCK WASHER	5
				1	328666	FERRULE	4
				1	50793-8	CRIMP END ASSY	3
				1	2-329106-1	GASKET	2
				1	329803	JACK ASSY	1
-71	-22	-21	-00		PART NO	DESCRIPTION	ITEM

RELEASED FOR PUBLICATION

THIS DRAWING IS UNPUBLISHED.

BY AMP INCORPORATED. ALL RIGHTS RESERVED.

DIMENSIONS: mm	DWN	M. O'BRINE	13DEC99	MATERIAL	-	FINISH	-
	CHK	B. MOYER	13DEC99	AMP Incorporated Harrisburg, PA 17105-3608			
TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD	B. MOYER	13DEC99				
0 PLC ±-	PRODUCT SPEC			CONNECTOR, COAXIAL, RF JACK			
1 PLC ±-	APPLICATION SPEC			BULKHEAD, SERIES BNC			
2 PLC ±-	WEIGHT			SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
3 PLC ±-	-			A4	00779	C- 330060	-
4 PLC ±-	-			CUSTOMER DRAWING			
ANGLES ±-	-			SCALE	SHEET	1 OF 1	REV F