



PS-89675-3260	PRODUCT SPECIFICATION
ES-89675-1580	CABLE ASSEMBLY INSTR.
MIL-STD-348A, FIG. 310.1	INTERFACE
SPECIFICATION	DESCRIPTION

73251-0452	73251-0450, PACKAGED BT TRAY (20 CAV.)
73251-0451	WITHOUT HEAT SHRINK TUBE
73251-0450	WITH HEAT SHRINK TUBE
PART NO.	DECIPTION

REMOVE 73251-0453
 EC NO: URF2008-0040
 2007/08/14
 DRW: NIELIN
 2007/08/17
 CHKD:
 APPR: MJIANG
 2007/08/17

QUALITY SYMBOLS
 ▽=0
 ▽=0

DESCRIPTION

A3

GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE MM/IN	SCALE	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
4 PLACES ± --- ± ---	mm INCH	DRAWN BY TEF	DATE 2000/11/09	TITLE SMA PLUG, STR 50 OHMS, RG316 SMA-PC
3 PLACES ± --- ± ---		CHECKED BY SSS	DATE 2000/11/09	molex MOLEX INCORPORATED
2 PLACES ± --- ± ---		APPROVED BY GMH	DATE 2000/11/09	
1 PLACE ± --- ± ---		ANGULAR ± 2 °		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SIZE C		SEE TABLE
		DOCUMENT NO. SD-73251-045		SHEET NO. 1 OF 1