




THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD		
K		EC-0G3C-0734-04	20DEC04	BSV	JG		



- 1 CONTACTS ARE LATCHED INTO THE PRELOAD WINDOWS
- 2 USE WITH #26-#30 AWG WIRE SIZE, .054/.030 INSULATION DIAMETER, .015 MAXIMUM INSULATION THICKNESS
- 3 THE DIMENSION APPLIES WITH THE FORWARD PRELOAD STOP IN CONTACT WITH THE HOUSING SURFACE
- 4 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 5 FOR INDIVIDUAL ASSEMBLIES SEE PART NUMBER 103897
- 6 ASSEMBLIES ARE JOINED BY THE CARRIER STRIP. ORDER QUANTITY REFLECTS TOTAL NUMBER OF INDIVIDUAL ASSEMBLIES REQUIRED. SEE TABLE FOR NUMBER OF ASSEMBLIES PER STRIP.
- 7 POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE BEAMS)
- 8 MAXIMUM ALLOWABLE BOW OF ASSEMBLY NOT TO EXCEED .055.
- 9 .000030 GOLD IN THE CONTACT AREA, .000050-.000100 BRIGHT TIN-LEAD ON THE TERMINATION AREA, ALL OVER .000050 NICKEL.
- 10 .000030 GOLD IN THE CONTACT AREA, .000050-.000100 MATTE TIN ON THE TERMINATION AREA, ALL OVER .000050 NICKEL.



EXAMPLE: STRIP ASSEMBLY
SCALE 3:1

10	2	2.40	1.198	1-104257-1	12	6-103961-1
10	2	2.20	1.098	1-104257-0	11	6-103961-0
10	2	2.00	.998	104257-9	10	5-103961-9
10	2	1.80	.898	104257-8	9	5-103961-8
10	2	1.60	.798	104257-7	8	5-103961-7
10	2	1.40	.698	104257-6	7	5-103961-6
10	4	2.39	.598	104257-5	6	5-103961-5
10	4	1.99	.498	104257-4	5	5-103961-4
10	5	1.99	.398	104257-3	4	5-103961-3
10	8	2.40	.298	104257-2	3	5-103961-2
10	10	2.00	.198	104257-1	2	5-103961-1
9	2	2.40	1.198	1-104257-1	12	1-103961-1
9	2	2.20	1.098	1-104257-0	11	1-103961-0
9	2	2.00	.998	104257-9	10	103961-9
9	2	1.80	.898	104257-8	9	103961-8
9	2	1.60	.798	104257-7	8	103961-7
9	2	1.40	.698	104257-6	7	103961-6
9	4	2.39	.598	104257-5	6	103961-5
9	4	1.99	.498	104257-4	5	103961-4
9	5	1.99	.398	104257-3	4	103961-3
9	8	2.40	.298	104257-2	3	103961-2
9	10	2.00	.198	104257-1	2	103961-1
PLATING	6	B	A	HOUSING PART NUMBER	NO OF POSN	ASSEMBLY PART NUMBER ON STRIP

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN L A MAYER 11-4-86
 CHK P de Jong 11-12-86
 APVD J SCHIEFER 11-13-86

TOLERANCES UNLESS OTHERWISE SPECIFIED:
 0 PLC ± -
 1 PLC ± -
 2 PLC ± .02
 3 PLC ± .005
 4 PLC ± -
 ANGLES ± -
 FINISH SEE TABLE

108-25034
 114-25026

RCPT ASSY, AMPMODU MTE, SINGLE ROW, .100 C/L ROW, .100, LATCHED & POLARIZED, FOR #26-#30 AWG WIRE SIZE, STRIP FORM

SIZE A2 CAGE CODE 00779 DRAWING NO C=103961

WEIGHT -
 CUSTOMER DRAWING

SCALE 4:1 SHEET 1 OF 1 REV K