



1 FINISH: PLATED GOLD .000050 THK PER ASTM-B-488 ON MATING END FOR A LENGTH OF .120 MIN WITH A POINT OF PLATING THICKNESS MEASUREMENT .060 FROM MATING END OF CONTACT; TAILS PLATED TIN-LEAD; ALL OVER NICKEL PER AMS QQ-N-290.

2 FINISH: PLATED GOLD .000050 THK PER ASTM-B-488 ON MATING END FOR A LENGTH OF .120 MIN WITH A POINT OF PLATING THICKNESS MEASUREMENT .060 FROM MATING END OF CONTACT; TAILS PLATED TIN; ALL OVER NICKEL PER AMS QQ-N-290.

2.900 [73.66]	29	3.050 [77.47]	3.450 [87.63]	3.750 [95.25]	120	6-446080-8
3.100 [78.74]	31	3.250 [82.55]	3.650 [92.71]	3.950 [100.33]	128	6-446080-7
4.900 [124.46]	49	5.050 [128.27]	5.450 [138.43]	5.750 [146.05]	200	6-446080-0
1.700 [43.18]	17	1.850 [46.99]	2.250 [57.15]	2.550 [64.77]	72	2-446080-2
OBSOLETE .900 [22.86]	9	1.050 [26.67]	1.450 [36.83]	1.750 [44.45]	40	2-446080-1
OBSOLETE 1.600 [40.64]	16	1.750 [44.45]	2.150 [54.61]	2.450 [62.23]	68	2-446080-0
OBSOLETE 2.400 [60.96]	24	2.550 [64.77]	2.950 [74.93]	3.250 [82.55]	100	1-446080-9
2.900 [73.66]	29	3.050 [77.47]	3.450 [87.63]	3.750 [95.25]	120	1-446080-8
3.100 [78.74]	31	3.250 [82.55]	3.650 [92.71]	3.950 [100.33]	128	1-446080-7
OBSOLETE 3.400 [86.36]	34	3.550 [90.17]	3.950 [100.33]	4.250 [107.95]	140	1-446080-6
OBSOLETE 3.700 [93.98]	37	3.850 [97.79]	4.250 [107.95]	4.550 [115.57]	152	1-446080-5
OBSOLETE 3.900 [99.06]	39	4.050 [102.87]	4.450 [113.03]	4.750 [120.65]	160	1-446080-4
OBSOLETE 4.100 [104.14]	41	4.250 [107.95]	4.650 [118.11]	4.950 [125.73]	168	1-446080-3
4.400 [111.76]	44	4.550 [115.57]	4.950 [125.73]	5.250 [133.35]	180	1-446080-2
OBSOLETE 4.700 [119.38]	47	4.850 [123.19]	5.250 [133.35]	5.550 [140.97]	192	1-446080-1
4.900 [124.46]	49	5.050 [128.27]	5.450 [138.43]	5.750 [146.05]	200	1-446080-0
OBSOLETE 5.300 [134.62]	53	5.450 [138.43]	5.850 [148.59]	6.150 [156.21]	216	446080-9
OBSOLETE 5.400 [137.16]	54	5.550 [140.97]	5.950 [151.13]	6.250 [158.75]	220	446080-8
OBSOLETE 5.700 [144.78]	57	5.850 [148.59]	6.250 [158.75]	6.550 [166.37]	232	446080-7
OBSOLETE 5.900 [149.86]	59	6.050 [153.67]	6.450 [163.83]	6.750 [171.45]	240	446080-6
OBSOLETE 6.400 [162.56]	64	6.550 [166.37]	6.950 [176.53]	7.250 [184.15]	260	446080-5
OBSOLETE 6.600 [167.64]	66	6.750 [171.45]	7.150 [181.61]	7.450 [189.23]	268	446080-4
OBSOLETE 6.900 [175.26]	69	7.050 [179.07]	7.450 [189.23]	7.750 [196.85]	280	446080-3
OBSOLETE 7.200 [182.88]	72	7.350 [186.69]	7.750 [196.85]	8.050 [204.47]	292	446080-2
OBSOLETE 7.400 [187.96]	74	7.550 [191.77]	7.950 [201.93]	8.250 [209.55]	300	446080-1
E	D	C	B	A	POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. DIM: TIM WIEST 3-28-89
 CHK: D. STONER 4-3-89
 TOLERANCES UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS: INCHES
 0 PLC ± -
 1 PLC ± .01
 2 PLC ± .01
 3 PLC ± .005
 4 PLC ± -
 ANGLES ± -
 MATERIAL: SEE CALLOUTS
 FINISH: SEE CALLOUTS

TYCO Electronics
 Tyco Electronics Corporation
 Harrisburg, Pa 17105-3608

PRODUCT SPEC
 APPLICATION SPEC
 NAME: PIN HEADER ASSEMBLY, FOUR ROW BOX, RIGHT ANGLE, W/ MOUNTING
 SIZE: A1
 CASE CODE: 00779
 DRAWING NO: 446080
 RESTRICTED TO: -
 CUSTOMER DRAWING
 SCALE: 4:1
 SHEET: 1 OF 1
 REV: H